


WMS

Manual Fork Over Stacker

Ideal and standard series for manual transport and lifting, with its different mast options and diverse lifting capacity enables to deal with a large number of applications in the warehouse or an other facilities.

- ◆ Optional choice of fixed bended fork (560/685X1150mm).
- ◆ Easy and comfortable handling through ergonomically handles, effortless pulling during transport with long tiller.
- ◆ We can offer additional protection for the operator through foot protection on the steering rollers.



- ◆ Safe parking in any situation with mechanical parking brake.
- ◆ Optional tiller pumping lifting and foot pedal lifting.



SPECIFICATIONS

MODEL			WMS500-1600				WMS1000				WMS1500				WMS2000-1600			
FEATURE																		
1.1	Capacity	Q kg	500				1000				1500				2000			
1.2	Load Center	C mm	600				600				600				400			
DIMENSIONS																		
2.1	Lifting height	h mm	1600				1600	2000	2500	3000	1600	2000	2500	3000	1600			
2.2	Mast lowered height	H mm	1970				2010	1520	1770	2020	2060	1520	1770	2020	2100			
2.3	Mast extend height	H1 mm	1970				2010	2510	3010	3510	2060	2510	3010	3510	2100			
2.4	Mast type		S				S	D	D	D	S	D	D	D	S			
2.5	Lowered height of fork	h1 mm	90				90				90				90			
2.6	Fixed fork outside distance	W mm	560	680			560		680		560		680		560	680		
2.7	Option adjustable fork, adjustable range	mm	330-870		330-680		330-870		330-680		330-870		330-680		330-870		330-680	
2.8	Fork length	sllell mm	1150				1150				1150				1150			
2.9	Overall width	W2 mm	720				780	870	870	870	780	870	870	870	780			
2.10	Overall length	L mm	1650				1650				1650				1650			
2.11	Lifting speed	mm/time	≥20				≥16				≥14				≥16			
2.12	Lowering speed		Controllable				Controllable				Controllable				Controllable			
2.13	Turing Radius	Wr mm	1540				1590				1590				1590			
WHEEL																		
3.1	wheel(drive/load) Type		PU/Nylon				PU/Nylon				PU/Nylon				PU/Nylon			
3.2	size of steering wheel	∅D mm	∅ 180*50				∅ 180*50				∅ 180*50				∅ 180*50			
3.3	size of Loading wheel	∅d mm	∅ 78*60				∅ 78*60				∅ 78*60				∅ 78*60			

